

# access

LIGHTING

## INSTALLATION INSTRUCTIONS

### IMPORTANT

Before assembling your **ACCESS LIGHTING** fixture, please make sure that you carefully read through these instruction sheets. Consider having your fixture installed by a qualified licensed electrician.



**NOTE:** The important safeguards and instructions that appear in this manual are not meant to cover all possible conditions and situations that may occur. It must be understood that common sense, caution and care, are factors that can't be built into any product. These factors must be supplied by the person(s) caring for and operating the fixture.

### GENERAL INFORMATION

All electrical connections must be in accordance with all ordinances, Local and National Electrical Codes. These fixtures are intended for mounting to a standard 4" x 2 1/2" metal octagon outlet box. The box must be directly supported by the building structure and U.L. Recognized.

### STEP BY STEP INSTRUCTIONS

Before starting your installation disconnect the Power by turning off the Circuit Breaker or by removing the fuse at the fuse box. Just turning the light off at the light switch is not sufficient to prevent electrical shock.



**COLLECTION**  
GLOW

**APPLICATION**  
Pendant Fixture

**MODEL NO.**  
28101  
28102

### WHAT WE PROVIDE

- Crossbar
- Mounting Hardware
- 1 x Glass Shade

### WHAT YOU NEED

- Screwdriver
- Wire Cutters
- Wiring Supplies as Specified by Electrical Code
- 1 x 60W E26 A19 Bulb (28101)
- 1 x 100W E26 A19 Bulb (28102)


### MAKE WIRE CONNECTIONS

Expose the supply wires from the outlet box.

Gently pull the supply wires through the hole in the crossbar. Connect the black supply wire to the black fixture wire. Secure with the supplied wire nut.

Connect the white supply wire to the white fixture wire. Secure with the supplied wire nut. Either wrap the green wire around one of the protruding screws or connect it to the supply ground wire. Secure all wires with electrical tape (not supplied).


Tuck all wires carefully into the J-Box



2

**MOUNT THE CROSSBAR AND CANOPY**


Mount the crossbar to the J-box with the supplied screws.  
 Hold the canopy up to the crossbar.  
 Align the holes of the canopy and secure with the supplied screw knobs.



3

**INSTALL GLASS SHADE AND INSERT THE BULB**

Hold the glass shade fitting over the socket and secure with the supplied socket ring.  
 Insert the bulb .  
 MAXIMUM WATTAGE 60W / 100W.  
 DO NOT EXCEED THE RECOMMENDED WATTAGE AS STATED ON THE WARNING LABEL AND INSTRUCTION SHEETS.



4

**RESTORE THE ELECTRICITY AND CHECK THE OPERATION OF YOUR NEW ACCESS LIGHTING FIXTURE**

**CAUTION** Please ensure that the fitting is cool and switched off before replacing the bulb. DO NOT use bulbs that might exceed the maximum wattage, stated on caution label.